

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 October 2005 (13.10.2005)

PCT

(10) International Publication Number
WO 2005/095546 A1

(51) International Patent Classification⁷: **C10B 25/00**,
9/00, 7/14, 39/00

(74) Agent: FESSENMAIER, Martin; Rutan & Tucker, LLP,
611 Anton Blvd., Suite 1400, Costa Mesa, CA 92626 (US).

(21) International Application Number:
PCT/US2004/008350

(22) International Filing Date: 17 March 2004 (17.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **FLUOR
TECHNOLOGIES CORPORATION** [US/US]; One En-
terprise Drive, Aliso Viejo, CA 92656 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ODER, John, W.**
[US/US]; Fluor Corporation, One Fluor Daniel Drive, Sug-
arland, TX 77478 (US). **ANTALFFY, Leslie, P.** [US/US];
Fluor Corporation, One Fluor Daniel Drive, Sugarland, TX
77478 (US). **MARTIN, Samuel, A.** [US/US]; Fluor Cor-
poration, One Fluor Daniel Drive, Sugarland, TX 77478
(US). **KIRKPATRICK, Kenneth, D.** [US/US]; Fluor Cor-
poration, One Fluor Daniel Drive, Sugarland, TX 77478
(US). **KNOWLES, Michael, B.** [US/US]; Fluor Corpora-
tion, One Fluor Daniel Drive, Sugarland, TX 77478 (US).
WEST, George, T. [US/US]; Fluor Corporation, One Fluor
Daniel Drive, Sugarland, TX 77478 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- with amended claims

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: VALVE INSTALLATION APPARATUS AND METHODS

(57) Abstract: A deheader valve is fitted onto an existing or new coke drum by initially positioning the body and valve, and then raising the valve to mate with the flange using a lifting device other than a chain fall. The vertical positioning of the deheader valve is preferably accomplished with a hydraulic or pneumatic piston, winch, scissor jack, ratchet jack, screw jack, and so forth. The distance traveled by the valve using these devices is more than 2 cm, commonly at least 20 cm, and in some installations up to 40 cm or more. In retrofit situations an oil inlet is provided in a side wall of the drum above the bottom drum flange.



WO 2005/095546 A1